




NOTES:

1. SUBSTRATE
2. SURFACE S1 IS TO BE PARALLEL TO SURFACE S2 WITHIN 3 ARCMIN
3. COATING (APPLY ACROSS CLEAR APERTURE)  
WAVELENGTH RANGE: 400 - 700nm
4. FINE GRIND SURFACE
5. POWER IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS  
APPLY ACROSS CLEAR APERTURE
6. RoHS COMPLIANT

**FOR INFORMATION ONLY:  
DO NOT MANUFACTURE  
PARTS TO THIS DRAWING**



BULLSEYE TYPE FILTER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE  
DIMENSIONS ARE FOR REFERENCE ONLY

**EO**® Edmund Optics®

REV A	S1	S2	THIRD ANGLE PROJECTION		TITLE	OD 0.04 - 1.0 , $\varnothing 25$ mm APODIZING FILTER REVERSE BULL'S EYE	
SHAPE	PLANO	PLANO	ALL DIMS IN	mm	DWG NO	64387	SHEET 1 OF 1
SURFACE QUALITY	60-40	60-40					
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED					