

NOTES:

1. SUBSTRATE
2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN 5 arcsec
3. COATING (APPLY ACROSS COATING APERTURE)
PERFORMANCE SPECIFICATIONS:
T(avg): >85% FROM 400 - 680nm FOR RANDOM POLARIZATION @ 45° AOI
T(abs): >80% FROM 400 - 680nm FOR ALL POLARIZATIONS @ 45° AOI
R(avg): >97% FROM 725 - 900nm FOR RANDOM POLARIZATION @ 45° AOI
R(abs): >95% FROM 725 - 900nm FOR ALL POLARIZATIONS @ 45° AOI
T(abs): = 50% 700nm @ 45° AOI





GDD: $80 \pm 30\text{fs}^2$ @ 450 - 680nm
 $120 \pm 80\text{fs}^2$ @ 400 - 680nm

S1: HARD COATED
 S2: SINGLE LAYER MgF2

4. FINE GRIND SURFACE

5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS
APPLY ACROSS CLEAR APERTURE
6. TRANSMITTED WAVEFRONT DISTORTION RMS@ 632.8nm $\leq \frac{1}{4} \lambda$
7. ROHS COMPLIANT

**FOR INFORMATION ONLY:
 DO NOT MANUFACTURE
 PARTS TO THIS DRAWING**




SHORTPASS FILTER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
 DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2
SHAPE	PLANO	PLANO
SURFACE QUALITY	40-20	40-20
CLEAR APERTURE	Ø22.00	Ø22.00
COATING APERTURE	Ø24.00	Ø24.00
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

Edmund Optics®

THIRD ANGLE
 PROJECTION



TITLE

700nm, 25mm Diameter, Low GDD Dichroic
 Shortpass Ultrafast Filter

DWG NO

14002

SHEET
 1 OF 1

ALL DIMS IN

mm