

## NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO < 1ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(AVG) ≤1.75% @ 400 - 700nm



- 5. Rohs Compliant
- 6. SURFACE FLATNESS (P-V): λ/4 (per inch over clear aperture)







## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE (mm)	Ø22.86	Ø22.86
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

			Edmund Optic	S®
THIRD ANGLE PROJECTION		TITLE	25.4mm DIA., 2mm THICK, MgF2 COA λ/4 N-BK7 WINDOW	ATED
ALL DIMS IN	mm	DWG NO	15428	SHEET 1 OF

25.4mm DIA., 2mm THICK, MgF2 COATED λ/4 N-BK7 WINDOW			
15428	SHEET 1 OF 1		