




NOTES:

1. SUBSTRATE: UV GRADE FUSED SILICA
2. COATING (APPLY ACROSS CLEAR APERTURE)  
 S1 & S2: R(ABS) < 0.25% @ 532nm  
 R(ABS) < 0.25% @ 1064nm  
 R(AVG) < 1.0% @ 500 - 1100nm
3. SURFACE S2 TO BE PARALLEL WITH S1 TO <5 ARCSEC

 FINE GRIND SURFACE

5. RoHS COMPLIANT




**FOR INFORMATION ONLY:  
DO NOT MANUFACTURE  
PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE  
DIMENSIONS ARE FOR REFERENCE ONLY

 **Edmund Optics®**

	S1	S2
SHAPE	PLANO	PLANO
SURFACE QUALITY	20-10	20-10
CLEAR APERTURE	$\phi 24.00$	$\phi 24.00$
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED



TITLE	30mm DIA., 4mm THICK, YAG-BBAR COATED, $\lambda/10$ FUSED SILICA WINDOW	
DWG NO	13357	SHEET 1 OF 1