
NOTES:

1. SUBSTRATE:

HOYA GLASS: ND-006

2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN < 0.02 mm


FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING





3. FINE GRIND SURFACE

4. COATING SPECIFICATION: \$1 & \$2:R(AVG) ≤0.5% @ 600 - 1050nm

- 5. OPTICAL DENSITY: 4 +/-0.2 @400-700nm
- 6. TRANSMISSION (%): 0.01% AVERAGE FROM 400-700nm
- 7. ROHS COMPLIANT







SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

Edmund Optics ®

	S1	S2		TITLE	4 OD, 12.5mm DIA., NIR I COATED, ABSORPTIVE ND FILTER		
SHAPE	PLANO	PLANO	THIRD ANGLE PROJECTION				
SURFACE QUALITY	80-50	80-50		1		, assert in a right	OLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	13162	SHEET 1 OF 1