## NOTES:


1. SUBSTRATE MATERIAL: N-BK7


2. COATING (APPLY ACROSS CLEAR APERTURE)

\$1 & \$2: MgF2 (400-700nm) Ravg ≤1.75% @ 400 - 700nm

3. FINE GROUND EDGES

4. Rohs Compliant





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2	EFL	600		Edmund Optic	<b>C</b> R
SHAPE	CONVEX	PLANO	BFL	586	U		<b>5</b>
SURFACE QUALITY	120-80	120-80	THIRD ANGLE PROJECTION		TITLE	000mm Dis. v. (00mm Fa a sill as sill At a F0	
RADIUS	310	8				200mm Dia x 600mm Focal Length, MgF2 Coated, PCX Condenser Lens	
CLEAR APERTURE	Ø195.00	Ø195.00		1			
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	19916	SHEET 1 OF 1

