NOTES:


- 1. ALLOWABLE OPTICAL MATERIAL: **FUSED SILICA CORNING 7980**
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN 5 ARCMIN
- 3. COATING (APPLY ACROSS ENTIRE SURFACE) \$1&\$2: VIS-NIR (400-1000nm)

Rabs ≤0.25% @ 880nm Ravg ≤1.25% @ 400 - 870nm Ravg ≤1.25% @ 890 - 1000nm



SIX SIDEWALLS:

SURFACE ACCURACY: COMMERCIAL POLISH



PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

			_
	\$1	\$2	
SHAPE	PLANO	PLANO	THIRD ANGLE PROJECTION
IRREGULARITY AT 632.8nm	N/A	N/A	
SURFACE QUALITY	60-40	60-40	ALL DIMS IN



Edmund Optics®

TITLE	8mm Aperture x 100mm L, VIS-NIR Coated, Standard NA, Fused Silica Light Pipe	
DWG NO	23503	SHEET 14 OF 18

