

All Products / Optics / Fiber Optics

High Power Multimode Fiber Optic Patchcords



- Low-OH Silica Core, 0.22 Numerical Aperture (NA)
- SMA Connector and Standardized 2m Length
- 380 2200 Wavelength Range

Common Specifications

Physical & Mechanical Properties

2.00	Jacket Material:	Stainless Steel		
6.35				
3	•			
	0.22 0.02			
	380 - 2200			
Hardware & Interface Connectivity				
SMA				
	6.35	6.35 0.22 0.02 380 - 2200 ace Connectivity		

Technical Information

Products

Title	Stock Number	Price	Buy
200µm Low-OH Silica Core, 0.22 NA, High Power SMA Patch Cable, 2m	<u>#72-226</u>	₹14,013	1 In Stock
400µm Low-OH Silica Core, 0.22 NA, High Power SMA Patch Cable, 2m	<u>#72-227</u>	₹15,959	1 In Stock
600µm Low-OH Silica Core, 0.22 NA, High Power SMA Patch Cable, 2m	<u>#72-228</u>	₹17,906	3 ln Stock
800µm Low-OH Silica Core, 0.22 NA, High Power SMA Patch Cable, 2m	<u>#72-229</u>	₹21,798	1 In Stock



Copyright 2023, Edmund Optics India Private Limited, #267, Greystone Building, Second Floor, 6th Cross Rd, Binnamangala, Stage 1, Indiranagar, Bengaluru, Karnataka, India 560038

Phone: 1-800-363-1992:

www.edmundoptics.com