

1/4-20 Bumper (Package of 4), Sorbothane Bumpers



Stock #55-244 **6 In Stock**

1 MRP ₹4,869

Price inclusive of all taxes

ADD TO CART

Volume Pricing

Qty 1-2	₹4,869 each
Qty 3+	₹4,318 each
Need More?	Request Quote

Product Downloads

General

English **Type:**

1/4-20 **Note:**

Physical & Mechanical Properties

Thickness (mm):

25.40

Sorbothane

Construction:

38.10

Diameter (mm):

30-65 / bumper

Load Capacity (lbs):

Threading & Mounting

12.7

Thread Length (mm):

Regulatory Compliance

Compliant

RoHS 2015:

[View](#)

Certificate of Conformance:

United States

Country of Origin:

Imported By:

Edmund Optics India Private Limited
267, Greystone Building, Second Floor,
6th Cross Rd, Binnamangala,
Stage 1, Indiranagar, Bengaluru,
Karnataka, India 560038
Phone: +91- 80-6845 0000

Product Details

- Absorb and Dissipate Vibration
- Stabilize Equipment up to 152lbs
- English, Metric, or Universal Styles

Sorbothane® Mounts absorb (57% absorption efficiency) and dissipate energy (70% specific damping). The mounts reduce vibration to other components by isolating the vibrations within the material while absorbing multi-directional forces. These hemisphere mounts can stabilize equipment weighing up to 38 pounds (hemisphere mounts), 65 pounds (1/4-20 male bumper mounts), or 29.4 kg (M6 male bumper mounts). Sorbothane® Mounts measure 50mm dia. (top) x26mm thick. The top side of the hemisphere is tacky, while the other side is felt. 1/4-20 or M6 male bumper mounts measure 38.1mm dia. x25.4mm thick. The threaded screw measures 12mm long. All models have a hardness durometer value of 70. Each package contains 4 mounts.