

## 0.19 - 20 $\mu$ m, 110W, Thermopile Power & Energy Detector



0.19 - 20 $\mu$ m, 110W, Thermopile Power & Energy Detector

Stock #78-465 **NEW** 1 In Stock

1 MRP ₹2,33,640

Price inclusive of all taxes

**ADD TO CART**

### Volume Pricing

Qty 1-4	₹2,33,640 each
Qty 5+	₹2,10,276 each
Need More?	<a href="#">Request Quote</a>

### Product Downloads

Maximum Incident Energy Density (J/cm<sup>2</sup>, 10ns Pulses):

1

### General

UP19k-100F-H9-INT-D0 (US) **Model Number:**

Fan Cooled **Cooling Method:**

**Compatible Meters:**

## Physical & Mechanical Properties

54.2 x 54.2 x 55.6 **Dimensions (mm):**

160 **Weight (g):**

0.16 **Weight (kg):**

19 **Active Area (mm):**

## Optical Properties

190 - 20000 **Wavelength Range (nm):**

0.19 - 20 **Wavelength Range (µm):**

## Sensor

Thermopile **Type of Sensor:**

## Electrical

110,000 **Maximum Incident Beam Power (mW):**

110 **Maximum Incident Beam Power (W):**

45,000 **Maximum Incident Power Density (W/cm<sup>2</sup>):**

45 **Maximum Incident Power Density (kW/cm<sup>2</sup>):**

3 mW **Noise Level:**

## Regulatory Compliance

[View](#) **Certificate of Conformance:**

Canada **Country of Origin:**

**Imported By:**  
 Edmund Optics India Private Limited  
 267, Greystone Building, Second Floor,  
 6th Cross Rd, Binnamangala,  
 Stage 1, Indiranagar, Bengaluru,  
 Karnataka, India 560038  
 Phone: +91- 80-6845 0000

## Product Details

- Photodetectors, Thermopiles, and Pyroelectric Detectors Available
- Various Active Area Sizes Across a Wide Range of Sensitivities
- **Meterless** and **Wireless** Detectors Also Available

Gentec-EO Integra USB Power and Energy Detectors combine a power meter and detector in one convenient package while providing fast response times and accurate measurements for beam analysis. These detectors are designed with a USB connector for easy connection to a PC or other acquisition system and include user-friendly software allowing for control via PC or serial commands. Versatile pyroelectric energy detectors with broadband coatings are optimized for low to high power densities. Gentec-EO Integra USB Power and Energy Detectors can be used with a variety of laser powers ranging from the nanowatts to multi-kilowatts. These detectors are ideal for laser energy measurement, thermal imaging, and remote sensing applications.