

[See all 76 Products in Family](#)

# LightPath 352240 | 9.94mm Dia., 0.50 NA, BBAR (350-700nm), Molded Aspheric Lens

See More by [Lightpath®](#)



Precision Molded Aspheric Lenses

Stock **#47-144** CLEARANCE **20+ In Stock**

MRP ₹4,944

**i** Price inclusive of all taxes

**ADD TO CART**

Volume Pricing	
Qty 1+	₹4,944 each
Need More?	<a href="#">Request Quote</a>

## Product Downloads

### General

352240 **Lightpath Lens Code:**

Aspheric Lens **Type:**

Collimate or Focus Laser Light **Typical Applications:**

### Physical & Mechanical Properties

**Diameter (mm):**

9.94 ±0.015

Clear Aperture CA (mm):

8.00

Edge Thickness ET (mm):

1.56

Center Thickness CT (mm):

3.69 ±0.04

Bevel:

Protective as needed

## Optical Properties

Effective Focal Length EFL (mm):

8.00 @ 780nm

Numerical Aperture NA:

0.50

Substrate: □

[ECO-550](#)

Focal Length Tolerance (%):

±1

Aspheric Design Wavelength (nm):

780

Coating:

BBAR (350-700nm)

Coating Specification:

R<sub>avg</sub> ≤0.5% @ 350 - 700nm

Asphere Figure Error (µm RMS):

Diffraction Limited Transmitted Wavefront

Surface Quality:

40-20

f#:

1.00

Abbe Number (v<sub>d</sub>):

50.22

Index of Refraction (n<sub>d</sub>):

1.603

Wavelength Range (nm):

350 - 700

Working Distance (mm):

5.92

Conjugate Distance:

Infinite

Focal Length Specification Wavelength (nm):

780.00

Transmitted Wavefront Error (λ, RMS):

< 0.040

## Material Properties

Coefficient of Thermal Expansion CTE (10<sup>-6</sup>/°C):

11.1

## Environmental & Durability Factors

Operating Temperature (°C):

≤200

## Regulatory Compliance

RoHS 2015:

[Compliant](#)

Certificate of Conformance:

[View](#)

Reach 233:

[Compliant](#)

Country of Origin:

China

Imported By:

Edmund Optics India Private Limited  
267, Greystone Building, Second Floor,  
6th Cross Rd, Binnamangala,  
Stage 1, Indiranagar, Bengaluru,  
Karnataka, India 560038  
Phone: +91- 80-6845 0000

## Product Details

- Eliminate Spherical Aberration

- Multiple Coating Options Available
- Range of Numerical Apertures

LightPath® Geltech™ Molded Aspheric Lenses are used to eliminate spherical aberration and improve focusing and collimating accuracy in a variety of laser applications. Low NA aspheric lenses are designed to maintain beam shape, while high NA lenses gather all available light to maintain beam power over long distances. LightPath® Geltech™ Molded Aspheric Lenses are ideal for applications including sighting systems, bar code scanners, laser diode-to-fiber coupling, optical data storage, or biomedical lasers.



## Technical Information

