

[See all 76 Products in Family](#)

# LightPath 355390 | 4.5mm Dia., 0.55 NA, BBAR (1050-1600nm), Molded Aspheric Lens

See More by [Lightpath®](#)



Precision Molded Aspheric Lenses

Stock **#66-927** **20+ In Stock**

[Other Coating Options](#)

- 1 + MRP ₹7,567

**i** Price inclusive of all taxes

**ADD TO CART**

| Volume Pricing |                               |
|----------------|-------------------------------|
| Qty 1-10       | ₹7,567 each                   |
| Qty 11-49      | ₹6,810 each                   |
| Need More?     | <a href="#">Request Quote</a> |

Product Downloads

**General**

355390 **Lightpath Lens Code:**

Aspheric Lens **Type:**

Collimate or Focus Laser Light **Typical Applications:**

## Physical & Mechanical Properties

4.50 ±0.015 **Diameter (mm):**

3.6 **Clear Aperture CA (mm):**

1.13 **Edge Thickness ET (mm):**

1.90 ±0.04 **Center Thickness CT (mm):**

Protective as needed **Bevel:**

## Optical Properties

2.75 @ 830nm **Effective Focal Length EFL (mm):**

0.55 **Numerical Aperture NA:**

**Substrate:**   
[D-ZLaF52LA](#)

±1 **Focal Length Tolerance (%):**

830 **Aspheric Design Wavelength (nm):**

BBAR (1050-1600nm) **Coating:**

R<sub>abs</sub> <1.0% @ 1050 - 1600nm **Coating Specification:**

40-20 **Surface Quality:**

0.91 **f#:**

40.79 **Abbe Number (v<sub>d</sub>):**

1.806 **Index of Refraction (n<sub>d</sub>):**

1050 - 1600 **Wavelength Range (nm):**

2.16 **Working Distance (mm):**

Infinite **Conjugate Distance:**

830.00 **Focal Length Specification Wavelength (nm):**

< 1.30 **Transmitted Wavefront Error (λ, RMS):**

## Material Properties

6.9 **Coefficient of Thermal Expansion CTE (10<sup>-6</sup>/°C):**

## Environmental & Durability Factors

≤200 **Operating Temperature (°C):**

## Regulatory Compliance

[Compliant](#) **RoHS 2015:**

[View](#) **Certificate of Conformance:**

[Compliant](#) **Reach 247:**

China **Country of Origin:**

Edmund Optics India Private Limited  
267, Greystone Building, Second Floor,  
6th Cross Rd, Binnamangala,  
Stage 1, Indiranagar, Bengaluru,  
Karnataka, India 560038  
Phone: +91- 80-6845 0000 **Imported By:**

## Product Details

- Eliminate Spherical Aberration
- Multiple Coating Options Available
- Range of Numerical Apertures

LightPath® Geltech™ Molded Aspheric Lenses are used to eliminate spherical aberration and improve focusing and collimating accuracy in a variety of laser applications. Low NA aspheric lenses are designed to maintain beam shape, while high NA lenses gather all available light to maintain beam power over long distances. LightPath® Geltech™ Molded Aspheric Lenses are ideal for applications including sighting systems, bar code scanners, laser diode-to-fiber coupling, optical data storage, or biomedical lasers.



## Technical Information

