

[See all 5 Products in Family](#)

Coherent® USB PowerMax Pro Measurement System 1295921 | 150W (Recertified 05-P)

See More by [Coherent®](#)



Coherent USB-PowerMax Pro Fast Measurement Systems

Stock **#37-075-RCD-05P** RECERTIFIED **1 In Stock**

-

1

+

MRP ₹3,26,869

Price inclusive of all taxes

ADD TO CART

Volume Pricing	
Qty 1+	₹3,26,869 each
Need More?	Request Quote

Product Downloads

General	
1295921	Model Number:
Meterless	Type:
≤10	Rise Time (µs):
±2	Calibration Uncertainty (%):

Water/Air (intermittent)	Cooling Method:
≤10	Fall Time (μs):
Maximum Incident Energy Density: 33mJ/cm ² (10ns; 1064nm)	
Physical & Mechanical Properties	
30 x 30	Active Area (mm):
Optical Properties	
810	Calibration Wavelength (nm):
400 - 1100, 9000 - 11000	Wavelength Range (nm):
Electrical	
±3	Spectral Compensation Accuracy (%):
14	Maximum Incident Power Density (kW/cm ²):
200mW to 150W	Power Range (Water-Cooled):
Hardware & Interface Connectivity	
2.5	Length of Cable (m):
USB	Computer Interface:
Regulatory Compliance	
View	Certificate of Conformance:
United States	Country of Origin:
Edmund Optics India Private Limited 267, Greystone Building, Second Floor, 6th Cross Rd, Binnamangala, Stage 1, Indiranagar, Bengaluru, Karnataka, India 560038 Phone: +91- 80-6845 0000	Imported By:

Product Details

- Fastest Response Laser Power Measurement System Available
- Fully Integrated Plug-and-Play USB System
- Large Active Area for Full Beam Measurement

Coherent USB-PowerMax Pro Fast Measurement Systems incorporate a patented power sensor technology that delivers orders of magnitude faster response time than previously possible with thermal or pyro detector technology. The systems enable users to measure laser average power, peak power, and pulse energy, while viewing the pulse temporal profile of the beam. They are ideal for process control due to the instantaneous response to laser power variation and detailed pulse analysis, without impacting process throughput. Coherent USB-PowerMax Pro Fast Measurement Systems eliminate the need for a separate meter and feature a small form factor, simple implementation, and easy communication via direct USB interface, or wirelessly through available Android™ and iOS applications.