

[See all 67 Products in Family](#)

# LightPath 354240 | 1550nm Alignment, 0.50 NA Fiber Collimator w/ FC/PC Connector

See More by [Lightpath®](#)



Fiber Optic Collimator and Focuser Assemblies



Stock #83-727 **10 In Stock**

⊖ 1 ⊕ ₹19,170

**ADD TO CART**

### Volume Pricing

Qty 1-10	₹19,170 each
Qty 11-25	₹17,010 each
Qty 26-49	₹16,020 each
Need More?	<a href="#">Request Quote</a>

### Product Downloads

### General

354240 **Lightpath Lens Code:**  
Fiber Collimator **Type:**

Lens Included:

#37-104

## Physical & Mechanical Properties

8.00 Clear Aperture CA (mm):

8.00

Bevel:

Protective as needed

Construction:

304L Stainless Steel Housing

Housing Diameter (mm):

12.00

Housing Length (mm):

12.7

## Optical Properties

Effective Focal Length EFL (mm):

8.00 @ 1150nm

Numerical Aperture NA:

0.50

Substrate:

ECO-550

Coating:

BBAR (1050-1600nm)

Coating Specification:

R<sub>abs</sub> <1.0% @ 1050 - 1600nm

Surface Quality:

40-20

f#:

1.00

Wavelength Range (nm):

1050 - 1600

Conjugate Distance:

Infinite

Alignment Wavelength (nm):

1550

Transmitted Wavefront Error (λ, RMS):

< 0.080

## Hardware & Interface Connectivity

Connector:

FC/PC

## Threading & Mounting

Mount:

M12 x 0.5

## Regulatory Compliance

RoHS 2015:

Compliant

Certificate of Conformance:

[View](#)

Reach 247:

Compliant

Country of Origin:

China

Imported By:

Edmund Optics India Private Limited

## Product Details

- Easy to Integrate
- Models for FC/PC, FC/APC, and SMA Connections Available
- Four Wavelength Ranges Covering 350-1600nm

LightPath® Fiber Optic Collimators are designed to collimate light exiting a fiber to a desired beam diameter or spot size or to focus light into a fiber when used in reverse. The lenses are diffraction limited, so they can achieve spot sizes down to a few microns. Lenses also feature an antireflection coating for low back reflection. LightPath® Fiber Optic Collimators are designed so that they can be used in pairs to couple the input and output light of optical devices. Optimum performance for long-term use is ensured by the factory set and tested lens alignment. Typical applications can include use with fiber coupled lasers and pigtailed receptacles, as well as communications and data transfer.

## Technical Information

