

TECHSPEC<sup>®</sup> 15mm Dia. Protected Gold,  $\lambda$ /4 Mirror



Stock **#63-174** 20+ In Stock

-

1

+

₹5,722

ADD TO CART

| Volume Pricing |                               |
|----------------|-------------------------------|
| Qty 1-5        | ₹5,722 each                   |
| Qty 6-25       | ₹4,593 each                   |
| Qty 26-49      | ₹4,282 each                   |
| Need More?     | <a href="#">Request Quote</a> |

Product Downloads

General

Flat MirrorType:

Physical & Mechanical Properties

15.00Diameter (mm):

Commercial PolishBack Surface:

|                      |                             |
|----------------------|-----------------------------|
| +0.0/-0.25           | Dimensional Tolerance (mm): |
| Protective as needed | Bevel:                      |
| 85                   | Clear Aperture (%):         |
| Fine Ground          | Edges:                      |
| 2.00 ±0.25           | Thickness (mm):             |

|                                                         |                                |
|---------------------------------------------------------|--------------------------------|
| Optical Properties                                      |                                |
| λ/4                                                     | Surface Flatness (P-V):        |
| BOROFLOAT®                                              | Substrate: □                   |
| 60-40                                                   | Surface Quality:               |
| Ravg >96% @ 700 - 2000nm<br>Ravg >96% @ 2000 - 10,000nm | Coating Specification:         |
| Protected Gold (700-10000nm)                            | Coating:                       |
| Metal                                                   | Coating Type:                  |
| 0.7 - 10                                                | Wavelength Range (µm):         |
| 700 - 10000                                             | Wavelength Range (nm):         |
| 0.8 J/cm² @ 1064nm, 10ns                                | Damage Threshold, Reference: □ |

|                                     |                             |
|-------------------------------------|-----------------------------|
| Regulatory Compliance               |                             |
| Compliant                           | RoHS 2015:                  |
| View                                | Certificate of Conformance: |
| Compliant                           | Reach 247:                  |
| United States                       | Country of Origin:          |
| Edmund Optics India Private Limited | Importer:                   |

## Product Details

- Available in a Wide Range of Sizes and Shapes
- Precision Metallic Mirror Coatings
- [Contact Us](#) for Custom Sizes

TECHSPEC® λ/4 First Surface Mirrors feature a high reflectivity coating deposited on the front surface of the glass substrate. The coated surface should be oriented to reflect incident light. TECHSPEC λ/4 First Surface Mirrors are offered in circular, square, and rectangular dimensions. First surface mirrors are ideal for applications requiring the mirror to be mounted at 45° in order to produce a 90° bend in the light path. These first surface mirrors easily mount into a [range of optical mounts](#) to facilitate application integration. The mirrors have available coatings of enhanced aluminum, protected aluminum, protected silver, and protected gold.

**Note:** Surface flatness is measured before coating.

A range of mounts specifically compatible with individual TECHSPEC® First Surface Mirrors can be found on product web pages.

## Custom

Edmund Optics offers comprehensive custom manufacturing services for optical and imaging components tailored to your specific application requirements. Whether in the prototyping phase or preparing for full-scale production, we provide flexible solutions to meet your needs. Our experienced engineers are here to assist—from concept to completion.

Our capabilities include:

- Custom dimensions, materials, coatings, and more
- High-precision surface quality and flatness
- Tight tolerances and complex geometries
- Scalable production—from prototype to volume

Learn more about our [custom manufacturing capabilities](#) or submit an inquiry [here](#).

## Compatible Mounts