

## 2.00", English Rotary Stage



Stock #33-465 **1 In Stock**

- 1 + MRP ₹1,14,511

Price inclusive of all taxes

**ADD TO CART**

### Volume Pricing

Qty 1+	₹1,14,511 each
Need More?	<a href="#">Request Quote</a>

### Product Downloads

### General

English **Type:**

### Physical & Mechanical Properties

Rotary **Type of Movement:**

Ball Bearing **Guide System:**

44.4 x 44.4 **Stage Size (mm):**

<b>Travel (°):</b>	±5 (Fine), 360 (Coarse)
<b>Center Hole:</b>	0.25" Dia. Thru
<b>Construction:</b>	Aluminum top and base; steel tangent arm drive
<b>Increments (arcmin):</b>	12
<b>Load Capacity, Normal (lbs):</b>	10
<b>Load Capacity, Vertical (lbs):</b>	4
<b>Stage Size (inches):</b>	1.75 x 1.75
<b>Weight (lbs):</b>	1
<b>Table Diameter (inches):</b>	2

## Hardware & Interface Connectivity

<b>Type of Drive:</b>	Tangent Arm
-----------------------	-------------

## Threading & Mounting

<b>Mounting Threads:</b>	(12) 6-32 on 0.625", 1.125" & 1.50" dia. B.C.
--------------------------	---

## Regulatory Compliance

<b>RoHS 2015:</b>	Compliant
-------------------	-----------

<b>Certificate of Conformance:</b>	<a href="#">View</a>
------------------------------------	----------------------

<b>Country of Origin:</b>	United States
---------------------------	---------------

<b>Imported By:</b>	Edmund Optics India Private Limited 267, Greystone Building, Second Floor, 6th Cross Rd, Binnamangala, Stage 1, Indiranagar, Bengaluru, Karnataka, India 560038 Phone: +91- 80-6845 0000
---------------------	---

## Product Details

- Low Wear, Low Friction Movement with Coarse or Fine Adjustment
- 2 or 2.62" Diameter Stages with Tapped Mounting Holes
- Calibrated Dial with 12 Minute Vernier for Accurate Read-Out

Compact miniature stages provide low-friction rotary movement with both coarse and fine adjustment. This allows for quick rotation over a continuous 360° travel, plus precise angular adjustment at any selected position. Features include preloaded angular contact ball bearing system, a positive position lock, a 2.00" or 2.62" diameter stage with tapped mounting holes and a calibrated dial with sixminute vernier for accurate positional read-out. It can be combined with our compatible linear translation stages for multi-axis linear-rotary applications.

## Technical Information

