

20X EO HR Infinity Corrected Objective



20XEO HR Infinity Corrected Objective (#58-373)

Stock **#58-373** **2 In Stock**

-

1

+

MRP ₹3,63,204

Price inclusive of all taxes

ADD TO CART

Volume Pricing	
Qty 1-4	₹3,63,204 each
Qty 5+	₹3,45,150 each
Need More?	Request Quote

Product Downloads

General	
28-20-46-000	Model Number:
Compatible Tube Lens Focal Length (mm): Focal Length: 200mm	
Microscope Objective	Type:
Infinity Corrected	Style:

Physical & Mechanical Properties	
82.00	Length excluding Threads (mm):
34	Maximum Diameter (mm):
240.00	Weight (g):
Optical Properties	
0.32mm	Horizontal Field of View, 1/2" Sensor:
0.44mm	Horizontal Field of View, 2/3" Sensor:
11.00	Field Stop Diameter (mm):
10.00	Focal Length FL (mm):
20X	Magnification:
0.60	Numerical Aperture NA:
0.56	Resolving Power (µm):
1.50	Depth of Field (µm):
13.00	Working Distance (mm):
400 - 700	Wavelength Range (nm):
95	Parfocal Length (mm):
N/A	Immersion Liquid:

Threading & Mounting	
M26 x 36 TPI	Mounting Threads:

Environmental & Durability Factors	
+23 ±5	Operating Temperature (°C):
30 - 70%	Operating Humidity:


Regulatory Compliance	
Compliant	RoHS 2015:
View	Certificate of Conformance:
Compliant	Reach 235:
Singapore	Country of Origin:
Edmund Optics India Private Limited 267, Greystone Building, Second Floor, 6th Cross Rd, Binnamangala, Stage 1, Indiranagar, Bengaluru, Karnataka, India 560038 Phone: +91- 80-6845 0000	Imported By:

Product Details

- High Resolving Power
- Designed for use in Zoom Lens Systems
- Features Mitutoyo Standard M26 x 36 TPI Threads

EO High Resolution Infinity Corrected Objectives are designed for high resolution over a small field of view. These objectives feature Mitutoyo standard M26 x 36 TPI threads and a 95mm parfocal length which allows them to be used interchangeably with Mitutoyo microscopes and accessories. While usable with Mitutoyo microscopes and accessories, these objectives perform best when used in a zoom lens system. EO High Resolution Infinity Corrected Objectives feature near-diffraction limited on axis performance. For longer working distance objectives that can be used in Mitutoyo systems, see our [EO Infinity Corrected Long Working Distance Objectives](#).

Technical Information



;