

[See all 1 Products in Family](#)

# 25.4mm Dia., 2mm Thick, ISP Optics Gold Dichroic Beamsplitter

See More by [ISP Optics](#)



Stock **#25-033** CLEARANCE CONTACT US

-

1

+

₹29,070

ADD TO CART

| Volume Pricing |                               |
|----------------|-------------------------------|
| Qty 1+         | ₹29,070 each                  |
| Need More?     | <a href="#">Request Quote</a> |

Product Downloads

General

|                       |               |
|-----------------------|---------------|
| Standard Beamsplitter | Type:         |
| BSP-DI-25-2           | Model Number: |

Physical & Mechanical Properties

|       |                     |
|-------|---------------------|
| 85    | Clear Aperture (%): |
| Plate | Construction:       |

|                                                                                                             |                               |
|-------------------------------------------------------------------------------------------------------------|-------------------------------|
| 25.40 +0.00/-0.13                                                                                           | Diameter (mm):                |
| <3                                                                                                          | Parallelism (arcmin):         |
| 2.00 ±0.13                                                                                                  | Thickness (mm):               |
| Optical Properties                                                                                          |                               |
| S1: Beamsplitter Coating<br>T <sub>avg</sub> = 70% from 400 - 700nm<br>R <sub>avg</sub> = 95% from 3 - 12µm | Coating:                      |
| R <sub>avg</sub> >95% @ 3000 - 12000nm and T <sub>avg</sub> >70% @ 400 - 700nm                              | Coating Specification:        |
| 3000 - 12000                                                                                                | Reflection Wavelength (nm):   |
| N-BK7                                                                                                       | Substrate: □                  |
| λ/4 @ 633nm                                                                                                 | Surface Flatness (P-V):       |
| 60-40                                                                                                       | Surface Quality:              |
| 400 - 700                                                                                                   | Transmission Wavelength (nm): |
| Regulatory Compliance                                                                                       |                               |
| Compliant                                                                                                   | RoHS 2015:                    |
| View                                                                                                        | Certificate of Conformance:   |
| Compliant                                                                                                   | Reach 240:                    |
| Latvia                                                                                                      | Country of Origin:            |
| Edmund Optics India Private Limited                                                                         | Imported By:                  |

## Product Details

- Separate Visible Light from Infrared (3-12µm) Light
- Visible Transmitting/Infrared Reflecting and Visible Reflecting/Infrared Transmitting Designs
- Ideal for Combining Visible Guide Lasers with MMR Lasers

ISP Optics Infrared (IR) Dichroic Beamsplitters are used to separate visible light from infrared light, working deeper in the infrared than conventional hot and cold mirrors. The platinum dichroic beamsplitters reflect visible light while transmitting light between 3 – 12µm and have an Anti-Reflection (AR) coating on the back surface to increase throughput. The gold dichroic beamsplitters transmit visible light while reflecting infrared light between 3 – 12µm and can be used with an AOI from 0 to 45°. ISP Optics Infrared (IR) Dichroic Beamsplitters are ideal for combining guide lasers with mid-IR laser sources, such as QCL lasers, for applications including gas detection, mid-infrared photothermal microscopy, and infrared spectroscopy.