

TECHSPEC<sup>®</sup> 25mm Dia. x 20mm FL, Uncoated, Hybrid Asphere



TECHSPEC<sup>®</sup> Plastic Hybrid Aspheric Lenses

Stock **#65-991** CLEARANCE **20+ In Stock**  
[Other Coating Options](#)

-

1

+

₹5,216

ADD TO CART

| Volume Pricing |                               |
|----------------|-------------------------------|
| Qty 1+         | ₹5,216 each                   |
| Need More?     | <a href="#">Request Quote</a> |

Product Downloads

General

Aspheric LensType:

Physical & Mechanical Properties

25.00 +0.00/-0.10Diameter (mm):

23.00Clear Aperture CA (mm):

3.4Edge Thickness ET (mm):

|                      |                           |
|----------------------|---------------------------|
| 10.00 ±0.10          | Center Thickness CT (mm): |
| Protective as needed | Bevel:                    |
| Convex               | Shape of Back Surface:    |

Optical Properties

|                 |                                                                                              |
|-----------------|----------------------------------------------------------------------------------------------|
| 20.00 @ 587.6nm | Effective Focal Length EFL (mm):                                                             |
| 0.63            | Numerical Aperture NA:                                                                       |
| 13.89           | Back Focal Length BFL (mm):                                                                  |
| Zeonex E48R     | Substrate:  |
| 587.6           | Aspheric Design Wavelength (nm):                                                             |
| Uncoated        | Coating:                                                                                     |
| 60-40           | Surface Quality:                                                                             |
| 0.8             | f/#:                                                                                         |
| 120             | Radius R <sub>2</sub> (mm):                                                                  |
| 475 - 675       | Wavelength Range (nm):                                                                       |
| Infinite        | Conjugate Distance:                                                                          |

Environmental & Durability Factors

|            |                             |
|------------|-----------------------------|
| -30 to +70 | Operating Temperature (°C): |
|------------|-----------------------------|

Regulatory Compliance

|                                     |                             |
|-------------------------------------|-----------------------------|
| Compliant                           | Reach 191:                  |
| Compliant                           | RoHS 2015:                  |
| View                                | Certificate of Conformance: |
| United States                       | Country of Origin:          |
| Edmund Optics India Private Limited | Imported By:                |

## Product Details


- Color-Corrected Plastic Aspheres
- Diffractive Surface Minimizes Chromatic Aberration
- Low-Cost, Molded Design

TECHSPEC® Plastic Hybrid Aspheric Lenses are molded aspheric lenses with diffraction-limited designs that eliminate chromatic aberrations caused by broadband light sources. These hybrid aspheric lenses are ideal for imaging or ophthalmic applications, or for use with tunable lasers or broadband or multispectral illumination sources. The [aspheric lens](#) eliminates spherical aberration, while the diffractive surface features a negative optical dispersion to yield excellent color correction.

TECHSPEC Plastic Hybrid Aspheric Lenses are similar in performance, but offer several advantages to our [TECHSPEC Aspherized Achromatic Lenses](#). Hybrid aspheric lenses feature all-plastic, monolithic designs that are much lighter than comparable aspherized achromatic lenses. These optical lenses are also available in higher numerical apertures. However, plastic hybrid aspheric lenses are limited by the inherent diffraction efficiency of the aspheric surface, yielding lower overall transmission than comparable aspherized achromatic lenses.

These lenses won the 2011 Prism Award for Optics and Optical Components.

## Technical Information



Compatible Mounts