

[See all 8 Products in Family](#)

35mm FL, Corning® Varioptic® C-C Series C-Mount Liquid Lens



Stock #91-615 **NEW** [CONTACT US](#)

− 1 + MRP ₹1,58,769

1 Price inclusive of all taxes

ADD TO CART

Volume Pricing

Qty 1+	₹1,58,769 each
Need More?	Request Quote

Product Downloads

General

Type:

Contents of Kit:

Coming® Varioptic® C-C-39N0-A1-350 Lens

Optical Properties**Focal Length FL (mm):**

35.00

Working Distance (mm):

200 - ∞

Aperture (f/#):

f/5.5 - f/22

Lens Wavelength Range:

VIS

Sensor**Sensor Format:**

1.1"

Pixel Size (µm):

2.74

Threading & Mounting**Mount:**

C-Mount

Environmental & Durability Factors**Operating Temperature (°C):**

50

Storage Temperature (°C):

45

Regulatory Compliance**RoHS 2015:****Compliant****Certificate of Conformance:**[View](#)**Country of Origin:**

France

Imported By:

Edmund Optics India Private Limited
 267, Greystone Building, Second Floor,
 6th Cross Rd, Binnamangala,
 Stage 1, Indiranagar, Bengaluru,
 Karnataka, India 560038
 Phone: +91- 80-6845 0000

Product Details

- Electronically Controllable Focus
- Ideal For Machine Vision Applications
- Compatible With Up to 1.1", 20mpx Sensors
- C-Mount for Seamless Integration into Imaging Systems

Coming® Varioptic® C-C Series C-Mount Liquid Lens Evaluation Kits feature an electronically controllable liquid lens and integrated driver electronics in a compact, C-Mount design. With rapid switching times, no moving parts, and AR-Coatings for excellent transmission in the VIS and NIR, these lenses are an ideal solution for autofocus applications demanding clarity, durability, and speed. Designed for seamless integration into C-Mount machine vision and imaging systems, the lenses are compatible with sensors up to 1.1". Coming® Varioptic® C-C Series C-Mount Variable Focus Liquid Lenses' integrated electronics allow the lenses to be powered by a simple DC supply and controlled through RS-232, I²C, or SPI interfaces. Evaluation kits include Lenses, USB-M Universal, USB Cable, and Focuslab Software Control Software and Documentation Package.