See all 3 Products in Family

461nm Mini Single Stage Free-Space Optical Isolator

Mini Free-Space Optical Isolators

Stock **#72-624** CLEARANCE **1 In Stock**

- 1 + **MRP ₹2,27,799**

Price inclusive of all taxes

ADD TO CART

Volume Pricing	
Qty 1+	**₹2,27,799** each
Need More?	Request Quote

Product Downloads

General

Type:
Single Stage Optical Isolator

Style:
Faraday

Physical & Mechanical Properties

Length (mm):
10.00

Clear Aperture CA (mm):
1.5

Diameter (mm):

9.20

Optical Properties

Minimum Transmission (%):

>80

Design Wavelength DWL (nm):

461

Damage Threshold, By Design:

4 kW/cm^2 @ DWL

Minimum Isolation at Design Wavelength (dB):

>35

Environmental & Durability Factors

Operating Temperature (°C):

+15 to +40

Regulatory Compliance

Certificate of Conformance:

View

Country of Origin:

United States

Imported By:

Edmund Optics India Private Limited
267, Greystone Building, Second Floor,
6th Cross Rd, Binnamangala,
Stage 1, Indiranagar, Bengaluru,
Karnataka, India 560038
Phone: +91- 80-6845 0000

Product Details

- Small, <1cm³, Form Factor
- Greater than 70% Minimum Transmission and >30dB Minimum Isolation
- Input Apertures as Low as 1.60mm

Mini Free-Space Optical Isolators are designed around a less than 1cm³ form factor with an incorporated Faraday Rotator while maintaining a superior performance with high isolation, transmission, and power densities. These isolators effectively reduce feedback in the external cavity of diode laser systems and blocks reflections from free-space fiber coupling. Designed to be resistant to environmental temperature changes these isolators are capable of integration into systems with where fluctuating temperatures are a concern. Mini Free-Space Optical Isolators increase power stabilization in optical systems and also eliminate feedback-induced damage to sensitive optical components. These isolators are ideal for quantum technology applications such as quantum communication, simulation, cryptography, sensors, computing, and networks.

;