

[See all 17 Products in Family](#)

## 5° Fan Angle, 500 - 850nm AR Coated, High Precision Powell Lens



Stock #70-137 [CONTACT US](#)

- 1 + MRP ₹32,790

**i** Price inclusive of all taxes

**ADD TO CART**

| Volume Pricing |                               |
|----------------|-------------------------------|
| Qty 1-10       | ₹32,790 each                  |
| Qty 11-49      | ₹29,460 each                  |
| Need More?     | <a href="#">Request Quote</a> |

### Product Downloads

### General

Beam Shaping Lens **Type:**

### Physical & Mechanical Properties

8.90 +0.00/-0.15 **Dimensions (mm):**

8.90 +0.00/-2.00 **Height (mm):**

**Input Beam Diameter, 1/e<sup>2</sup> (mm):**

## Optical Properties

**N-BK7**      **Substrate:**

**BBAR (500-850nm)**      **Coating:**

**500 - 850**      **Wavelength Range (nm):**

**R<sub>abs</sub> <1.0% @ 500 - 700nm**  
**R<sub>abs</sub> <1.5% @ 700 - 850nm**      **Coating Specification:**

**1.458**      **Index of Refraction (n<sub>d</sub>):**

**5.00**      **Fan Angle (°):**

## Regulatory Compliance

**View**      **Certificate of Conformance:**

**United States**      **Country of Origin:**

**Edmund Optics India Private Limited**  
**267, Greystone Building, Second Floor,**  
**6th Cross Rd, Binnamangala,**  
**Stage 1, Indiranagar, Bengaluru,**  
**Karnataka, India 560038**  
**Phone: +91- 80-6845 0000**      **Imported By:**

## Product Details

- Generate Uniform, Flat-Top Profile Over Entire Line
- Fan Angles from 1° to 75° Available
- AR Coated for 400 - 500nm or 500 - 850nm

Precision Powell Lenses, also known as aspheric line generators (ALGs), spread an input beam across a uniform line with a top-hat beam profile at a specified fan angle. These Powell lenses are produced through a precision manufacturing process to ensure high contained power, uniformity, and line straightness across the entire produced line, as well as superior part-to-part consistency. They are designed for a specific input beam diameter to provide best line uniformity; larger input beams will result in higher intensity at the ends of the generated line, while smaller will create a more Gaussian distribution. Precision Powell Lenses are ideal for use in machine vision and life science applications including 3D profile measurement, PCB inspection, line-scan SD-OCT, line-scan confocal microscopy, flow cytometry, and particle analysis.