



[See all 5 Products in Family](#)

Everix Ultra-Thin OD 2 Longpass Filter, 500nm, 12.5mm Square

See More by [Everix](#)



Stock **#35-123** CLEARANCE [CONTACT US](#)

-

1

+

₹5,912

ADD TO CART

Volume Pricing	
Qty 1+	₹5,912 each
Need More?	Request Quote

Product Downloads

General	
Flexible Filter	Type:
Physical & Mechanical Properties	
12.5 x 12.5	Dimensions (mm):
12.50	Length (mm):

12.50	Width (mm):
±0.1	Dimensional Tolerance (mm):
>90	Clear Aperture (%):
Optical Properties	
2.0 (absolute)	Optical Density OD (Average):
500.00	Cut-On Wavelength (nm):
>85 (average)	Transmission (%):
±3 typical	Cut-On Tolerance (%):
Regulatory Compliance	
Compliant	RoHS 2015:
View	Certificate of Conformance:
United States	Country of Origin:
Edmund Optics India Private Limited	Imported By:

Product Details

- Ultra-Thin, Flexible Substrate
- Sharp Cut-On Wavelength Designs
- Extruded Thin Film, Insensitive to Scratches

Everix Ultra-Thin Longpass Filters combine high performance and low cost in a new class of thin film interference filters that are flexible, scratch insensitive, and ultra-thin (200 - 500µm). These filters feature cut-on wavelengths in the visible range with cut-on tolerances of ±3% typical and >85% average transmission. The flexible extruded thin film filters are complex multilayer filters, which excel across a variety of needs, including longpass, edge, and notch filters. Everix Ultra-Thin Longpass Filters are ideal for demanding vision and medical technology applications.

Note: Custom filter designs can be purchased directly from [Everix](#).

Technical Information

