

[See all 13 Products in Family](#)

# 50mm Dia., 0.4mm Thick, SCHOTT D263® T eco Window

See More by [SCHOTT Optical Components](#)



Stock **#18-300** **8 In Stock**

-

1

+

₹2,751

ADD TO CART

| Volume Pricing |                               |
|----------------|-------------------------------|
| Qty 1-5        | ₹2,751 each                   |
| Qty 6-25       | ₹2,219 each                   |
| Qty 26-99      | ₹2,054 each                   |
| Need More?     | <a href="#">Request Quote</a> |

Product Downloads

| General                          |                         |
|----------------------------------|-------------------------|
| Protective Window                | Type:                   |
| Physical & Mechanical Properties |                         |
| 45.00                            | Clear Aperture CA (mm): |
| 50.00 ±0.25                      | Diameter (mm):          |

|                      |                        |
|----------------------|------------------------|
| 0.40 ±0.05           | Thickness (mm):        |
| Protective as needed | Bevel:                 |
| 90                   | Clear Aperture (%):    |
| Fine Ground          | Edges:                 |
| 0.21                 | Poisson's Ratio:       |
| 72.9                 | Young's Modulus (GPa): |

| Optical Properties |                                        |
|--------------------|----------------------------------------|
| Uncoated           | Coating:                               |
| D263® T eco        | Substrate: □                           |
| 1.523              | Index of Refraction (n <sub>d</sub> ): |
| 80-50              | Surface Quality:                       |
| 350 - 2000         | Wavelength Range (nm):                 |

| Material Properties |                                                              |
|---------------------|--------------------------------------------------------------|
| 2.51                | Density (g/cm³):                                             |
| 557                 | Transformation Temperature (°C):                             |
| 7.2 (+20 to +300°C) | Coefficient of Thermal Expansion CTE (10 <sup>-6</sup> /°C): |


| Regulatory Compliance               |                             |
|-------------------------------------|-----------------------------|
| Compliant                           | RoHS 2015:                  |
| View                                | Certificate of Conformance: |
| Compliant                           | Reach 247:                  |
| United States                       | Country of Origin:          |
| Edmund Optics India Private Limited | Imported By:                |

## Product Details

- Thin 0.4mm SCHOTT D263® T eco Substrates
- Excellent Glass Alternative to Plastic Optics
- Ideal for Weight and Space Sensitive Applications

SCHOTT D263® T eco Windows feature thin 0.4mm thick, eco-friendly manufactured glass substrates with high transmission in the visible and near-infrared (NIR) spectra. These windows are manufactured through a precision down-draw manufacturing process, achieving surface roughness <1nm RMS with excellent thickness tolerances and low total thickness variation (TTV). SCHOTT D263® T eco glass has high chemical resistance and environmental durability and is an excellent alternative to plastic in automotive and electronics applications requiring lightweight optics. SCHOTT D263® T eco Windows are ideal for use as cover glass for resistive touch panels, substrates for capacitive touch sensors, or as substrates for optical filters used in mobile devices or LiDAR units.

## Technical Information



## Custom

Edmund Optics offers comprehensive custom manufacturing services for optical and imaging components tailored to your specific application requirements. Whether in the prototyping phase or preparing for full-scale production, we provide flexible solutions to meet your needs. Our experienced engineers are here to assist—from concept to completion.

Our capabilities include:

- Custom dimensions, materials, coatings, and more
- High-precision surface quality and flatness
- Tight tolerances and complex geometries
- Scalable production—from prototype to volume

Learn more about our [custom manufacturing capabilities](#) or submit an inquiry [here](#).

## Quote Your Size

---