

8mm CA, Corning® Varioptic® V-PE Series Variable Focus and Astigmatism Liquid Lens Development Kit



Corning® Varioptic® V-PE Series Variable Focus Liquid Lenses



Stock **#74-503** **3 In Stock**

-

1

+

MRP ₹1,02,147

Price inclusive of all taxes

ADD TO CART

Volume Pricing	
Qty 1+	₹1,02,147 each
Need More?	Request Quote

Product Downloads

General	
Development Kit	
Type:	
Development Kit	
Contents of Kit:	
Corning® Varioptic® V-PE-80RO-07 Lens USB-MUniversal (with V-PE connector and USB compatibility) USB-B to USB-ACable Visalab Software Control Software Documentation Package (USB-Stick)	
D-V-PE-80R0-07	
Model Number:	
Typical Applications:	
Compact optical systems providing tunable power : Sphere, Cylinder and Axis	
Physical & Mechanical Properties	
27.00 (packaged lens)	
Diameter (mm):	

8.0	Clear Aperture CA (mm):
7.80 (packaged lens)	Thickness (mm):
Optical Properties	
VS	Coating:
-12 to +12 diopter (Sphere Only) -6 to +6 diopter (Sphere using Cylinder) -5 to 0 diopter(Cylinder Only)	Focus Range (mm):
95 @ 587nm	Transmission (%):
300nm	Transmitted Wavefront Error, RMS:
Environmental & Durability Factors	
+10 to +40	Operating Temperature (°C):
-40 to +55	Storage Temperature (°C):
Regulatory Compliance	
View	Certificate of Conformance:
France	Country of Origin:
Edmund Optics India Private Limited 267, Greystone Building, Second Floor, 6th Cross Rd, Binnamangala, Stage 1, Indiranagar, Bengaluru, Karnataka, India 560038 Phone: +91- 80-6845 0000	Imported By:

Product Details

- Combine a Liquid Lens with Dedicated, Calibrated Driver Board
- Temperature Compensation and Response Time Optimization Features
- Include Control Software and Documentation Package
- [A-P Series Liquid Lenses](#) Also Available

Coming® Varioptic® A-PE & V-PE Series Variable Focus Liquid Lens Development Kits feature a variable focus liquid lens with a dedicated, calibrated driver board for enhanced performance, temperature compensation, and response time optimization, as well as all necessary cables and control software for operation. The driver board enables advanced features including temperature compensation algorithms, response time optimization for optical power changes, and sweep mode which acquires clear images while the liquid lens is still in motion. The V-PE Series expands on this technology with an 8-electrode design, enabling independent control of spheres at ±24 diopters of power, cylinders at ±5 diopters of power, and axis for astigmatism correction without any moving parts, ensuring silent, reliable operation. Coming® Varioptic® A-PE & V-PE Series Variable Focus Liquid Lenses are ideal for use in barcode readers, industrial inspection, medical imaging, and biometrics applications and are fully compatible with the [AF Explorer Camera](#) for plug-and-play operation. Also included in the development kit is a documentation package with additional application information.