

[See all 7 Products in Family](#)

# Coherent® High-Sensitivity Thermopile Sensor PS10 1098350 | 1W Max Power

See More by [Coherent®](#)



Coherent® High-Sensitivity Thermopile Sensors

Stock **#12-416** **2 In Stock**

MRP ₹1,89,567

**1** Price inclusive of all taxes

**ADD TO CART**

Volume Pricing	
Qty 1+	₹1,89,567 each
Need More?	<a href="#">Request Quote</a>

## Product Downloads

### General

**Model Number:**  
PS10 Coherent Part Number: 1098350

**Type:**  
[Meter required](#)

**Linearity (%):**  
±1

**Calibration Uncertainty (%):**  
1

Air	<b>Cooling Method:</b>
2	<b>Response Time (s):</b>
<b>Note:</b> Includes a Removable Light Tube to Minimize Background Radiation Effects	
<b>Compatible Meters:</b> <a href="#">#35-203</a> , <a href="#">#12-393</a> , <a href="#">#59-978</a> , <a href="#">#88-411</a> , <a href="#">#66-277</a> , <a href="#">#88-412</a>	
<b>Maximum Incident Energy Density:</b> 50mJ/cm <sup>2</sup> (10ns, 1064nm)	
<b>Physical &amp; Mechanical Properties</b>	
10	<b>Active Area Diameter (mm):</b>
<b>Optical Properties</b>	
514	<b>Calibration Wavelength (nm):</b>
300 - 11000	<b>Wavelength Range (nm):</b>
0.3 - 11	<b>Wavelength Range (μm):</b>
<b>Sensor</b>	
Thermopile	<b>Type of Sensor:</b>
<b>Electrical</b>	
0.5	<b>Maximum Incident Power Density (kW/cm<sup>2</sup>):</b>
100μW - 1W	<b>Power Range:</b>
1	<b>Maximum Power (W):</b>
10μW	<b>Power Resolution:</b>
<b>Hardware &amp; Interface Connectivity</b>	
2	<b>Length of Cable (m):</b>
DB-25	<b>Computer Interface:</b>
<b>Environmental &amp; Durability Factors</b>	
Yes	<b>Thermally Stabilized:</b>
<b>Regulatory Compliance</b>	
<a href="#">Exempt</a>	<b>RoHS 2015:</b>
<a href="#">Contains SVHC(s)</a>	<b>Reach 224:</b>
<a href="#">View</a>	<b>Certificate of Conformance:</b>
United States	<b>Country of Origin:</b>
<b>Imported By:</b> Edmund Optics India Private Limited 267, Greystone Building, Second Floor, 6th Cross Rd, Binnamangala, Stage 1, Indiranagar, Bengaluru, Karnataka, India 560038 Phone: +91- 80-6845 0000	

## Product Details

- Broad Spectral Range with High Sensitivity and High Resolution
- Large Active Area Sensors up to 19mm in Diameter
- Flat Broadband Output with No Saturation above 1mW/cm<sup>2</sup>

Coherent® High-Sensitivity Thermopile Sensors are designed to have a broad spectral response to accommodate an array of lasers with different wavelengths. The large active area and high resolution of these thermopile sensors allows for accurate measurements of low-power lasers. A range of models are available to meet specific needs relating to thermal stability, background radiation, and air current effect. Coherent® High-Sensitivity Thermopile Sensors are designed to accurately measure the laser power of small laser diodes, HeNe lasers, and small ion lasers. Unique to this design, these sensors will not saturate when laser power exceeds 1mW/cm<sup>2</sup>.

