

[See all 14 Products in Family](#)

Conductive Tape, Copper, 1/2" 18 Feet



Indium Tin Oxide (ITO) Coated Conductive Windows

Stock #90-013 **NEW** 1 In Stock

1 MRP ₹4,742

Price inclusive of all taxes

ADD TO CART

Volume Pricing

Qty 1+	₹4,742 each
Need More?	Request Quote

Product Downloads

General

Conductive Tape **Type:**

Meets Military ML-T-470102 and UL 510 test specification. **Note:**

Physical & Mechanical Properties

0.5 **Width (inches):**

Optical Properties

Coating Specification:

<100 Ω/sq

Environmental & Durability Factors

Operating Temperature (°C):

-40 to 162

Regulatory Compliance

RoHS 2015:

[Compliant](#)

Certificate of Conformance:

[View](#)

Reach 250:

[Compliant](#)

Country of Origin:

United States

Imported By:

Edmund Optics India Private Limited
267, Greystone Building, Second Floor,
6th Cross Rd, Binnamangala,
Stage 1, Indiranagar, Bengaluru,
Karnataka, India 560038
Phone: +91-80-6845 0000

Product Details

- Electro Magnetic Interference (EMI) Shielding, Defogging, and Display Protection Applications
- 10Ω/sq and 100Ω/sq Coating Options
- 12.5, 25, 50, and 75 mm Sizes Available
- Conductive Tape Available for Prototyping

Indium Tin Oxide (ITO) Coated Conductive Windows feature an electrically conductive coating on float glass substrates and are available in sheet resistivities of 10 Ω/sq and 100 Ω/sq. A low sheet resistivity of 10 Ω/sq is ideal for applications requiring high conductivity, while the 100 Ω/sq resistivity is commonly used for improved heat dissipation and NIR transmission. Available in both round and square sizes from 12.5 to 75 mm, the windows feature up to 88% visible light transmission in the 400-700nm range. Indium Tin Oxide (ITO) Coated Conductive Windows are ideal for a wide variety of applications including display protection, EMI shielding, outdoor surveillance, de-fogging, and de-icing applications. Additionally, conductive tape is available to simplify prototyping and integration.