

Edmund Optics® Autocollimator



Stock #03-658 **2 In Stock**

- 1 + MRP ₹2,33,109

i Price inclusive of all taxes

ADD TO CART

Volume Pricing

Qty 1+	₹2,33,109 each
Need More?	Request Quote

Product Downloads

General

Type of Optics:

Achromat: 40mm Diameter x250mm EFL
Eyepiece: 21.5mm FL

Light Source Included:

#222 Lens End Lamp

Optical Properties

Angle Tolerance (arcmin):

±55 Off-Axis
Gradations: 5

Hardware & Interface Connectivity

Power Supply:

Plug-In Adapter 120 VAC to 2.3 VAC

Threading & Mounting

Mounting Threads:

1/4-20

Regulatory Compliance

Certificate of Conformance:

[View](#)

Country of Origin:

United States

Imported By:

Edmund Optics India Private Limited
267, Greystone Building, Second Floor,
6th Cross Rd, Binnamangala,
Stage 1, Indiranagar, Bengaluru,
Karnataka, India 560038
Phone: +91- 80-6845 0000

Product Details

- 5 Arcmin Resolution
- Economical Design
- 1/4-20 Tap Hole for Mounting to Optical Bench Posts

The Edmund Optics® Autocollimator is comprised of an achromatic objective, a light source, a reticle, a beamsplitter, and an eyepiece with a reticle calibrated in small angle increments. The reticle pattern, a crosshair, is projected onto a reflective surface. The returning reflected beam is diverted, via the beamsplitter, to the calibrated eyepiece. The deviation in angle from the perpendicularity of the reflective surface is precisely measured at the eyepiece. The Edmund Optics Autocollimator has many applications, such as measuring extremely small angles and calibrating and aligning various optical instruments and components. Other uses include measuring small deflections and vibrations.

The autocollimator has a 1/4-20 tap hole for mounting to optical bench posts and positioning equipment. It can also be mounted in a V-block or ring mount (tube O.D. is 1.85"). The Tubular Lamp Assembly is a self-contained unit comprising a precision reticle and a long-life lens-end lamp. The compact tubular configuration provides versatility to use as a light source for an optical instrument or as an optical test accessory. As a test accessory, it can be readily mounted in a "V" or ring mount used in conjunction with an optical bench or table.

Technical Information

