See all 14 Products in Family

Everix Ultra-Thin OD 2 Bandpass Filter, 660nm, 12.5mm Dia.

See More by Everix



Stock **#16-836** **6 In Stock**

- 1 + **MRP ₹7,718**

Price inclusive of all taxes

ADD TO CART

Volume Pricing	
Qty 1-10	**₹7,718** each
Qty 11+	**₹6,810** each
Need More?	Request Quote

Product Downloads

General

Type:

Flexible Filter

Physical & Mechanical Properties

Diameter (mm):

12.45 ±0.15

Clear Aperture (%):

>90

Maximum Thickness (µm):
400

Optical Properties

Optical Density OD (Average):
2.0

Center Wavelength CWL (nm):
660.00

Full Width-Half Max FWHM (nm):
31.60 (maximum)

Transmission (%):
>65% Average

Center Wavelength CWL Tolerance (%):
±2

Regulatory Compliance

Certificate of Conformance:
View

Country of Origin:
United States

Imported By:
Edmund Optics India Private Limited
267, Greystone Building, Second Floor,
6th Cross Rd, Binnamangala,
Stage 1, Indiranagar, Bengaluru,
Karnataka, India 560038
Phone: +91- 80-6845 0000

Product Details

- Designed for Common LED and Laser Diode Wavelengths
- Scratch Insensitive, Ultra-Thin Design
- Easily Integrated into Portable Devices

Everix Ultra-Thin Broadband Bandpass Filters are designed for common LED and laser diode wavelengths. With an exterior polymeric protective layer, these filters are scratch-insensitive, shatterproof, and easy to clean. These filters feature an average transmission of 65%, average optical density of 2.0, and maximum thickness of 400 µm. Ultra-Thin Broadband Bandpass Filters are created with a lightweight, ultra-thin design and can be easily integrated into portable systems, including point of care medical devices, AR/VR wearables, and spaceborne systems.

For more information on this patented ultra-thin filter technology, visit our **Everix brand page**.

Note: Custom filter designs can be purchased directly from **Everix**.

Technical Information



;