

[See all 5 Products in Family](#)

Germanium, 25.4mm, Uncoated, ISP Optics IR Right Angle Prism | GE-RP-25

See More by [ISP Optics](#)



Infrared (IR) Right Angle Prisms

Stock **#25-041** **9 In Stock**

1 ₹3,28,500

ADD TO CART

| Volume Pricing | |
|----------------|-------------------------------|
| Qty 1+ | ₹3,28,500 each |
| Need More? | Request Quote |

Product Downloads

General

Right Angle Prism **Type:**

GE-RP-25 **Model Number:**

Physical & Mechanical Properties

±0.25 **Dimensional Tolerance (mm):**

85.00 **Clear Aperture (%):**

Length of Hypotenuse (mm):

35.90

Length of Legs (mm):

25.40

Optical Properties

Coating:

Uncoated

Substrate:

Germanium (Ge)

Surface Quality:

60-40

Angle Tolerance (arcmin):

±10

Image Orientation:

Left-Handed

Ray Deviation (°):

90

Wavelength Range (nm):

2000 - 14000

Wavelength Range (µm):

2 - 14

Surface Flatness (P-V):

2λ

Regulatory Compliance

RoHS 2015:

Compliant

Certificate of Conformance:

[View](#)

Reach 240:

Compliant

Country of Origin:

Latvia

Imported By:

Edmund Optics India Private Limited


Product Details


- CaF₂, Ge, and ZnSe Substrates
- Ray Deviation of 90°
- Ideal for Use with Collimated Sources
- Additional [Infrared Optics](#) Available

ISP Optics Infrared (IR) Right Angle Prisms provide 90° or 180° redirection of laser beam or image paths depending on the input prism surface. Available with calcium fluoride (CaF₂), germanium (Ge), or zinc selenide (ZnSe) substrates, these right-angle prisms are ideal for a range of IR laser and imaging applications. CaF₂ offer a low refractive index and broad transmission range from 0.2 – 7µm, making it useful for applications requiring high transmission from the UV through the IR. Ge is transmissive from 2 – 14µm with a high index of 4.002 at 11µm and is used in applications where the optical path length needs to be maximized. ZnSe has high, even transmission from 0.6 - 18µm and is typically integrated with CO₂ laser systems that feature a 632.8nm HeNe alignment laser and 10.6µm output beam. ISP Optics Infrared (IR) Right Angle Prisms can be used in combination for beam/image displacement.

Note: Special care should be taken when handling Zinc Selenide as it is a toxic material. Always wear rubber or plastic gloves to avoid risk of contamination.

Technical Information






Right Angle Prism Ray Path



Right Angle Prism Ray Path



Right Angle Prism Tunnel Diagram



Right Angle Prism Tunnel Diagram

Special Handling

These optics require special handling to avoid damage and ensure long-term performance. Proper handling, cleaning, and storage are essential to maintain optical quality. Explore our [Optics Cleaning Resources](#) for step-by-step guides and best practices. For personalized assistance, [Email us](#) or [Chat](#) with our technical support team.



Component Handling Tools

