

## High Resolution Microscopy Resolution Target



High Resolution Microscopy Resolution Target, #37-539

Stock **#37-539** **3 In Stock**

1 **MRP ₹1,99,656**

Price inclusive of all taxes

**ADD TO CART**

Volume Pricing	
Qty 1-4	₹1,99,656 each
Qty 5+	₹1,89,705 each
Need More?	<a href="#">Request Quote</a>

### Product Downloads

### Physical & Mechanical Properties

**Dimensions (mm):**

10 x 10 x 1

**Construction:**

Stainless Steel, 75 x 25 x 1.5mm, microscope slide format

**Pattern:**

Pinholes Diameter: 4µm, 2µm, 1µm, 0.5µm, 0.25µm  
Line patterns: 58 groups, 7.5 - 3300 lp/mm  
Line Widths: 66.7µm - 0.152µm

Pattern Tolerance:

100nm/cm = 10<sup>-5</sup>

## Optical Properties

Substrate:

Fused Silica w/Chrome deposit

Optical Density OD (Average):

OD>7 @ 400nm, 6 @ 550nm, 4.5 @ 750nm, 3.6 @ 1000nm

Spectral Range:

200 - 2000nm

## Regulatory Compliance

RoHS 2015:

Compliant

Certificate of Conformance:

[View](#)

Reach 233:

Compliant

Country of Origin:

Germany

Imported By:

Edmund Optics India Private Limited  
267, Greystone Building, Second Floor,  
6th Cross Rd, Binnamangala,  
Stage 1, Indiranagar, Bengaluru,  
Karnataka, India 560038  
Phone: +91- 80-6845 0000

## Product Details

- Small Pattern Sizes - 100nm and 3300 lp/mm
- Composed using High-Precision E-Beam Lithography
- Negative Pattern Design

High Resolution Microscopy Slide Targets are designed using high-precision e-beam lithography. The patterns are etched on a 10 × 10mm<sup>2</sup> fused silica substrate with broad spectral transmission (DUV-VIS-NIR), on which a chromium layer of high optical density is applied. By removing the chromium layer, patterns are created in sizes down to 100nm. High Resolution Microscopy Slide Targets provide excellent dimensional stability and are mounted in a metal microscope slide holder. The negative patterns on each target allow the structures to be transparent, while the background is blocked by a chrome layer.

### High Res Microscopy USAF Target

High Res Microscopy USAF Targets easily determine the resolution limit of an objective in transmitted light and consists of 59 line patterns with 7.5 to 3300 lp/mm in horizontal and vertical alignment. This target also features 5 pinholes with diameters between 4.0-0.25µm, which allows for detailed characterization of micro-imaging optics.

### High Res Microscopy Star Target

High Res Microscopy Star Targets consist of 5 Siemens stars and show the peculiarity that the tapered segments in the center of the stars are precisely manufactured to a minimum width of 150nm. This target is ideal for the determining the resolution of microscope objectives with very high numerical apertures.

### High Res Microscopy Checker Board

High Res Microscopy Checker Board features a total size of 9.0 x 9.0mm<sup>2</sup> out of 50 x 50µm<sup>2</sup> squares. The checker board is ideal for testing of image skew and curvature, along with determining image quality due to the straight and sharp edges.