

[See all 15 Products in Family](#)

Laser Safety Window LS02 ARG 100 x 200mm



Laser Safety Windows

Stock **#29-373** **2 In Stock**

MRP ₹8,815

Price inclusive of all taxes

ADD TO CART

Volume Pricing	
Qty 1-9	₹8,815 each
Qty 10+	₹7,965 each
Need More?	Request Quote

Product Downloads

General

EN 207/208 Ratings:

DLB7 and IR LB4 @ 180-315nm
DIRMLB6 @ 315-532nm

Filter Material:

Polymer

Filter:

LS02

Physical & Mechanical Properties

100 x 200

Dimensions (mm):

3.00

Thickness (mm):

Optical Properties

Optical Density OD (Average):
>7 @ 180 - 532nm

Amber

Color:

Visible Light Transmission VLT (%):
48 (Photopic), 9 (Scotopic)

Regulatory Compliance

Certificate of Conformance:
[View](#)

Country of Origin:
United States

Imported By:
Edmund Optics India Private Limited
267, Greystone Building, Second Floor,
6th Cross Rd, Binnamangala,
Stage 1, Indiranagar, Bengaluru,
Karnataka, India 560038
Phone: +91- 80-6845 0000

Product Details

- CE Certified Laser Radiation Protection
- Available for UV, VIS, and NIR Wavelengths
- 200mm x 100mm Size Ideal for Small Enclosures
- 304.8mm x 304.8mm Sizes Also Available

Laser Safety Windows feature high optical density in a specified wavelength range across the UV, VIS, and NIR spectra. Made from acrylic and polycarbonate, these laser safety windows are CE certified to protect against laser radiation. These windows are available in 200 x 100mm for easy integration into small equipment doors, windows, and enclosures. 304.8 x 304.8mm sizes are also available. Laser Safety Windows are ideal for blocking laser radiation while providing safe viewing of laser environments in materials processing, manufacturing, and laboratory applications featuring Nd:YAG, CO₂, fiber, and other laser sources.

Warning: Because of the potential for eye damage, the degree of protection required in each circumstance should be determined by the Laser Safety Officer, the industrial hygienist, or the individual responsible for the safety program.
