

[See all 36 Products in Family](#)

Lucid Vision Labs Atlas10 ATX450N-CT2, onsemi XGS 45000, 44.7MP, Color Camera

See More by [LUCID Vision Labs™](#)



LUCID Vision Labs Atlas10 10GigE Power over Ethernet (PoE) Cameras (Front, C-Mount)



Stock #74-734 **NEW** [CONTACT US](#)

- 1 + MRP ₹7,60,392

Price inclusive of all taxes

ADD TO CART

Volume Pricing	
Qty 1+	₹7,60,392 each
Need More?	Request Quote

Product Downloads

Color **Spectrum:**

General

Color Camera **Type:**

ATX450N-CT2 **Model Number:**

Lucid Vision Labs **Manufacturer:**

Atlas10 **Camera Series:**

Physical & Mechanical Properties

55 x 55 x 95.5 (excludes connectors and lens mount) **Dimensions (mm):**

304 **Weight (g):**

Full **Housing:**

Sensor

380MB **Image Buffer:**

2.2" **Sensor Format:**

45.00 **Resolution (Megapixels):**

16.00 **Frame Rate (fps):**

8,192 x 5,460 **Pixels (H x V):**

3.2 x 3.2 **Pixel Size, H x V (µm):**

26.21 x 17.47 **Sensing Area, H x V (mm):**

onsemi XGS 45000 **Imaging Sensor:**

Progressive Scan CMOS **Type of Sensor:**

Global **Shutter Type:**

12 bit **Pixel Depth:**

73.328µs to 10 s **Exposure Time:**

65.33 **Dynamic Range (dB):**

GigE Vision v2.0 **Machine Vision Standard:**

Electrical

11.5 (External Power Supply) <12 (PoE+) **Power Consumption (W):**

Hardware & Interface Connectivity

10GigE, M12 **Connector:**

Power Supply Required and Sold Separately:
USA: [#18-364](#)
Europe: [#18-364](#)
Japan: [#18-364](#)
Korea: Not Available
China: [#18-364](#) **Power Supply:**

1 opto-isolated input, 1 opto-isolated output, 2 non-isolated bi-directional ports **GPIOs:**

Hardware Trigger (GPIO), Software Trigger, or PTP (IEEE 1588) **Synchronization:**

Back Panel **Interface Port Orientation:**

8-pin MB **GPIO Connector Type:**

Threading & Mounting

TFL-II Mount **Mount:**

2 x ¼-20 with Tripod Mount Adapter [#17-120](#) **Mounting Threads:**

Environmental & Durability Factors

-20 to +55 **Operating Temperature (°C):**

Storage Temperature (°C):

-30 to +60

Regulatory Compliance

Certificate of Conformance:

[View](#)

Country of Origin:

Canada

Imported By:

Edmund Optics India Private Limited
267, Greystone Building, Second Floor,
6th Cross Rd, Binnamangala,
Stage 1, Indiranagar, Bengaluru,
Karnataka, India 560038
Phone: +91- 80-6845 0000

Product Details

- 10GBASE-T (10GigE) Ethernet Interface with PoE+
- 5.0 to 65 Megapixel Sony 4th Gen Pregius S Sensors
- Compact 55 x 55mm Form Factor
- TFL-Mount Compatible with some [TECHSPEC® CA Series FFL Lenses](#)

LUCID Vision Labs Atlas10 10GigE Power over Ethernet (PoE) Cameras combine 4th generation Sony Pregius S sensors with 10GigE interface, delivering fast frame rates at high resolution and image quality in a compact and rugged housing. The 10GBASE-T Power over Ethernet PoE+ interface allows for data transfer speeds of up to 1.2 GB/s and can also provide power to the camera over one CAT6a cable up to 25m in length. The high bandwidth enables these cameras to run at high bit depths (10/12-bit) to maximize image quality while maintaining smooth frame rates. The back-illuminated CMOS sensors offer high sensitivity, high dynamic range, and low noise, and are actively aligned to the lens mount at the same optical axis to minimize performance discrepancies resulting from sensor tilt and rotation. LUCID Vision Labs Atlas10 10GigE Power over Ethernet (PoE) Cameras are GigE Vision compliant and feature rugged M12 Ethernet and M8 GPIO connectors, making them ideal choices for industrial, automotive, factory automation, process control, and other machine vision applications requiring high resolutions and bandwidth.