

[See all 59 Products in Family](#)

LUCID Vision Labs Triton™ TRI124S-MC, Sony IMX545, 12.3MP, Monochrome Camera

See More by [LUCID Vision Labs™](#)



LUCID Vision Labs Triton™ Power over Ethernet (PoE) Cameras



Stock **#18-480** **1 In Stock**

[Similar Cameras](#)

1 MRP ₹1,06,731

Price inclusive of all taxes

ADD TO CART

Volume Pricing	
Qty 1+	₹1,06,731 each
Need More?	Request Quote

Product Downloads

Spectrum:
Monochrome

General

Type:
Monochrome Camera

Model Number:
TRI124S-MC

Lucid Vision Labs
Triton™

Manufacturer:
Camera Series:

Physical & Mechanical Properties

29 x 29 x 45 (excludes connectors and lens mount)
67

Dimensions (mm):
Weight (g):

Full

Housing:

Sensor

128MB
1/1.1"

Image Buffer:
Sensor Format:

12.30
9.00

Resolution (Megapixels):
Frame Rate (fps):

4,096 x 3,000
2.74 x 2.74

Pixels (H x V):
Pixel Size, H x V (µm):

11.22 x 8.22
Sony IMX545

Sensing Area, H x V (mm):
Imaging Sensor:

Progressive Scan CMOS
Global

Type of Sensor:
Shutter Type:

12 bit
35.50µs - 10s

Pixel Depth:
Exposure Time:

GigE Vision v2.0

Machine Vision Standard:

Electrical

2.5 (External Power Supply)
3.1 (PoE)

Power Consumption (W):

Hardware & Interface Connectivity

GigE (PoE)
GigE, M12

Interface:
Connector:

Power Supply Required and Sold Separately.
USA: [#18-364](#)
Europe: [#18-364](#)
Japan: [#18-364](#)
Korea: Not Available
China: [#18-364](#)

Power Supply:

1 opto-isolated input, 1 opto-isolated output, 2 non-isolated bi-directional ports

GPIOs:

Hardware Trigger (GPIO), Software Trigger, or PTP (IEEE 1588)

Synchronization:

Back Panel

Interface Port Orientation:

8-pin MB

GPIO Connector Type:

Threading & Mounting

C-Mount
1/4-20 with Tripod Mount Adapter [#11-474](#)

Mount:
Mounting Threads:

Environmental & Durability Factors

-20 to +55

Operating Temperature (°C):

Storage Temperature (°C):
-30 to +60

Regulatory Compliance

[View](#) Certificate of Conformance:

Country of Origin:
Canada

Imported By:
Edmund Optics India Private Limited
267, Greystone Building, Second Floor,
6th Cross Rd, Binnamangala,
Stage 1, Indiranagar, Bengaluru,
Karnataka, India 560038
Phone: +91-80-6845 0000

Product Details

- Compact 29 x 29 x 45mm Form Factor
- Global, Rolling, or Polarized CMOS Sensors
- IP67 Protection with Optional Lens Tubes

LUCID Vision Labs Triton™ GigE Power over Ethernet (PoE) Cameras provide exceptional price performance in a compact 29 x 29mm form factor. These cameras are available with Sony's Pregius™ and Starvis™ imaging sensors with up to 24.5 megapixels of resolution, as well as Sony's polarized sensor. Each imaging sensor is actively aligned during manufacturing, ensuring sharp and crisp images even in the corners. Using the accessory IP67 lens tubes (sold separately), LUCID Vision Labs Triton GigE Power over Ethernet (PoE) Cameras can operate in harsh environments where dust or water are present up to IP67 thresholds. Triton cameras are ideal for automotive, process control, and food and beverage applications.

;