

[See all 8 Products in Family](#)

Power Terminal Block, 2 pin, 5mm Pitch

See More by [Zaber™](#)



Power Terminal Block, 2 pin, 5mm Pitch

Stock #15-304 **2 In Stock**

1 MRP ₹505

Price inclusive of all taxes

ADD TO CART

Volume Pricing

Qty 1+	₹505 each
Need More?	Request Quote

Product Downloads

General

Cables & Power Supplies

Type:

Note:
Used to connect a customer's own power supply to Zaber's products that take 24-48 V

Hardware & Interface Connectivity

Power Supply:
Power Supply Required and Sold Separately.
USA: [#15-294](#)

Europe: [#15-294](#)
Japan: [#23-662](#)
Korea: [#33-773](#)
China: [#15-294](#)

Regulatory Compliance

Compliant **RoHS 2015:**

View **Certificate of Conformance:**

Compliant **Reach 247:**

China **Country of Origin:**

Imported By:
Edmund Optics India Private Limited
267, Greystone Building, Second Floor,
6th Cross Rd, Binnamangala,
Stage 1, Indiranagar, Bengaluru,
Karnataka, India 560038
Phone: +91- 80-6845 0000

Product Details

- Large 150mm Diameter Mounting Platform With 360° Continuous Rotation
- Contactless Direct Drive for High-Speed Silent Operation and Long Lifetime
- High Precision 0.01 Arc Second Encoder Resolution and 1µrad Minimum Step Size

Zaber™ High Speed Direct Drive Motorized Rotary Stage System combines a large 150mm diameter mounting platform with 360° continuous rotation supporting centered loads up to 10kg and rotation speeds up to 450RPM. These rotary stages' contactless direct drive design delivers high-speed, silent operation and long service life for demanding positioning and automation applications. For precision motion control, the stage provides 0.01 arc second encoder resolution and a 1 µrad minimum step size, enabling highly repeatable positioning. Zaber™ High Speed Direct Drive Motorized Rotary Stage System features a 50.8mm (2") diameter rotating aperture, providing added flexibility for optical, inspection, and through-hole system integration. This stage is also daisy-chain compatible with other Zaber products, simplifying multi-axis system setup and control.

Note: A 48 VDC universal power supply, data cables for daisy chaining, and computer interface cables (USB or RS-232) are sold separately as accessories.