

Tungsten-Halogen Spectroscopy Illuminator

See More by [Ocean Optics](#)



Stock #90-544 NEW CONTACT US

-
1
+
MRP ₹2,22,383

● Price inclusive of all taxes

ADD TO CART

Volume Pricing	
Qty 1+	₹2,22,383 each
Need More?	Request Quote

Product Downloads

General

Type:
Tungsten-Halogen Illuminator

Model Number:
HL-2000-LL-FHSA

Note:
Power supply, integrated shutter, integrated filter holder for filters up to 25 mm square or 25 mm round in diameter and 4 mm in thickness, and integrated attenuator included.
The illuminator has an optical output drift of <0.1% per hour

10000 **Operating Lifetime (hours):**

Physical & Mechanical Properties

0.5 **Weight (kg):**

58 x 59 x 140 **Dimensions (mm):**

Optical Properties

360 - 2400 **Wavelength Range (nm):**

Electrical

4.5 **Output Power (mW):**

Hardware & Interface Connectivity

SMA905 **Connector:**

12 VDC **Power Requirement:**

Environmental & Durability Factors

5 to 35 **Operating Temperature (°C):**

2800 **Color Temperature (K):**

5–95% without condensation at 40°C **Operating Humidity:**

Regulatory Compliance

Compliant **RoHS 2015:**

View **Certificate of Conformance:**

Compliant **Reach 250:**

China **Country of Origin:**

Imported By:
Edmund Optics India Private Limited
267, Greystone Building, Second Floor,
6th Cross Rd, Binnamangala,
Stage 1, Indiranagar, Bengaluru,
Karnataka, India 560038
Phone: +91- 80-6845 0000

Product Details

- Stable, High-Quality Output Across Broad Wavelength Ranges from 185–2500 nm
- Deuterium-Tungsten, Xenon, Tungsten-Halogen Lamp Types Available
- Fully Compatible with Ocean Optics Spectrometers and Accessories
- Recommended Patchcords Available [Here](#)

Ocean Optics Spectroscopy Illuminators offer a flexible range of UV–NIR light sources to pair with Ocean Optics spectroscopy systems. Choose from Tungsten-Halogen for stable VIS–NIR output (360–2400nm), Xenon for high-intensity, pulsed broadband UV–NIR illumination (185–2500nm), or Deuterium-Tungsten for continuous coverage from deep UV through NIR (210–2500nm). Typical applications include reflectance, transmittance, absorbance, and fluorescence measurements where reliable, well-matched illumination is essential. Ocean Optics Spectroscopy Illuminators are designed for lifetimes of up to 10,000 hours and feature SMA fiber connections.