


[See all 1 Products in Family](#)

Edmund Optics TPA Ultrafast Autocorrelator by APE (700-1100nm)



#11-760 Edmund Optics TPA Ultrafast Autocorrelator by APE (700-1100nm)



Stock #11-760 **1 In Stock**

⊖ 1 ⊕ ₹12,68,100

ADD TO CART

Volume Pricing	
Qty 1+	₹12,68,100 each
Qty 2+	₹11,41,245 each
Need More?	Request Quote

Product Downloads

General

10.2 x 10.2 **Dimensions (cm):**

<0.001 % of Scan Range **Delay Resolution:**

Collinear Intensity **Measurement Mode:**

Not Required	SHG Phase Matching:
300Hz - 50kHz	Trigger Mode:
Gaussian, Sech2, Lorentz	Fitting Routine:
Certified NIST Traceable Calibration	Calibration:

Physical & Mechanical Properties

6	Input Aperture (mm):
---	-----------------------------

Optical Properties

700 - 1100	Wavelength Range (nm):
50 - 3500fs	Measurable Pulse Duration:
Linear/Horizontal	Input Beam Polarization:
<1%	Delay Linearity:

Electrical

150fs - 15ps	Scan Range:
<0.1	Sensitivity (W^2):
>300	Repetition Rate (Hz):
300mW/5 μ J	Maximum Input Power/Energy:

Hardware & Interface Connectivity

USB	Computer Interface:
-----	----------------------------

Regulatory Compliance

View	Certificate of Conformance:
Germany	Country of Origin:
Edmund Optics India Private Limited	Imported By:

Product Details

- Trusted APE® Performance with Same Day Availability
- TPA Detector with $>0.1W^2$ Sensitivity @ 700 - 1100nm
- Includes a Controller with USB Interface and Ready to Use Data Acquisition Software
- Compact Design and Tuning Free Wavelength Matching
- Ideal for Low and High Repetition Rate Ultrafast Lasers

The Edmund Optics Ultrafast Autocorrelator by APE is used to characterize ultrafast laser pulses originating from Ti:sapphire and Yb:doped lasers. Featuring a built-in Two Photon Absorption (TPA) detector, this autocorrelator is ideal for measuring ultrafast femtosecond and picosecond laser pulses at wavelengths from 700 to 1100nm. The highly sensitive TPA detector allows for measurements of ultrafast laser pulses with high sensitivity by eliminating the need for angle tuning of the SHG nonlinear crystal. The Edmund Optics Ultrafast Autocorrelator by APE is designed with a compact form factor and can be mounted onto an adjustable optical mount for easy incorporation into any ultrafast optical setup. Each autocorrelator ships with a built-in TPA detector, a controller with USB-interface, ready to use data acquisition software, and TCP/IP-based software with a subset of SCPI standard based commands that allow for users to program automated measurement routines. The Edmund Optics Ultrafast Autocorrelator by APE is calibrated to a traceable standard in accordance with NIST (U.S. National Institute of Standards and Technology) measurement traceability specifications.

Technical Information

