

## Z-Axis Plate for 1.25" Stage (Side Drive-Standard)



Stock #54-370 **1 In Stock**

₹9,169

**ADD TO CART**

### Volume Pricing

Qty 1+	₹9,169 each
Need More?	<a href="#">Request Quote</a>

### Product Downloads

## SPECIFICATIONS

### General

Standard	<b>Note:</b>
1.25	<b>Compatible Stage Size (inches):</b>
Side Drive	<b>Stage Type:</b>

## Physical & Mechanical Properties

2.33	Length (inches):
1.25	Width (inches):
0.31	Thickness (inches):
0.15 R Oval	Bracket Thru-Hole:

## Regulatory Compliance

<a href="#">Compliant</a>	RoHS 2015:
<a href="#">View</a>	Certificate of Conformance:

## PRODUCT DETAILS


- Combine Ball Bearing Stages into 3 Axis Positioning Systems
- Designs for 1.25, 1.75, 2.62, and 5" Stages
- Aluminum Construction with Black Anodized Finish

We now offer a complete line of Z-axis brackets to combine ball bearing stages into three axis positioning systems. These brackets are currently included with all X-Y-Z low and standard profile stage configurations. By purchasing single-axis stages separately, the brackets can be used to configure your own X-Y-Z combination, using different drive options, travel options, and even standard or thru-hole mounting stage options. All brackets are designed for the same stage size and drive type (center or side). All Z-axis brackets include socket head cap screws (S.H.C.S.) to connect two ball bearing stages together; 4 screws for each bracket (#54-380 includes 6 screws; 2-Z, 4-Y). Brackets are designed for Z-axis mounting with tapped mounting holes to accept screws through the counterbored holes in stage bases. Y-axis mounting on the brackets is with clearance or counterbored holes for S.H.C.S. to connect directly to stage carriage mounting surfaces. Aluminum construction with black anodized finish. X-Y and X-Z configurations are possible. However, due to side locking screws and mounting stage configurations, not all options will work. All standard profile brackets have thru-hole clearance.

**Note:** #54-374 Z-Axis Plate for 1.75" Stages is for use with 1" or 25mm travel stages: #37-935, #37-936, #37-955, and #37-956.

## TECHNICAL INFORMATION

### 1.25" Z-Axis Adapter Plate (#54-370)



Units: inches

2 c'bored mtg. holes for #4 S.H.C.S.